

## Avantco A-49F-HC 54" Solid Door Reach-In Freezer

Item #178A49FHC



### Technical Data

Width	54 Inches
Depth	32 1/4 Inches
Height	82 1/2 Inches
Interior Width	49 3/8 Inches
Interior Depth	27 1/8 Inches
Interior Height	53 1/2 Inches
Amps	6.08 Amps
Hertz	60 Hertz
Phase	1 Phase
Voltage	115 Volts
Access Type	Doors
BTU (LBP)	2614
Capacity	41.3 cu. ft.
Casters	With Casters
Color	Silver
Compressor Location	Bottom Mounted
Construction	Stainless Steel and Aluminum
Door Style	Swing
Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors
Hinge Location	Left/Right
Horsepower	1 2/7 HP
Installation Type	Freestanding
Number of Doors	2 Doors
Number of Shelves	6 Shelves
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Sections	2 Sections
Temperature Range	-8 - -1 Degrees F
Type	Freezers

### Features

- Corrosion-resistant stainless steel exterior with aluminum interior
- Features 2 self-closing and stay-open locking doors
- Includes 6 epoxy coated shelves with 90 lb. capacity each
- Digital temperature controller with automatic defrost function
- Eco-friendly R290 refrigerant; 115V; 1 2/7 hp; 6.08 Amps

### Certifications



5-15P




ETL US



ETL Sanitation

## Plan View



## Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco A-49F-HC 54" solid door freezer, you receive performance you can depend on! A painted aluminum interior gives you increased durability, while (2) 430 stainless steel doors and exterior sides give it a sleek appearance. For convenience, 6 epoxy coated shelves feature shelf clips for customization when desired.

Designed to maintain temperatures from -8 to -1 degree Fahrenheit, this freezer boasts a bottom-mounted 1 2/7 hp compressor that uses eco-friendly R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an environmentally-responsible choice for your business. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include stay open doors with locks, automatic defrosting, and a digital temperature control with digital display. This item requires a 115V electrical connection for operation.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).